



Unparalleled Power and performance

Closed cycle hydraulic driving circuit, provide unparalleled power and performance. Driving system loop using the latest technology development level of axial variable piston pump and plunger drive motor.

Hydraulic tank provides a cooling system to prolong the service life of components, enhance the ability of corrosion resistance and improve the monitoring and control system performance.



Advantages:

- Length, Angle sensor built-in, anti-collision dustproof;
- Refined steel covering part's service life three times longer than ordinary primer;
- For the machine working in dusty, sand washing, spraying and corrosive site, provide the best protection in this industry.

GTBZ22J

Max. platform height	22.2m
Max. working height	24.2m
Max. horizontal reach	18m
Load capacity	250Kg (non-restricted)
Platform size(L × W × H)	1.45mX0.85mX1.24m
Overall dimension L × W × H(stowed)	11.2mx2.49mx2.84m
Overall weight	11952kg(2WD)/12022kg (4WD)

Easy to locate

Arm lift/fall & extend/retract and rotation of the chassis, using full scale gradient control, even in narrow space, it is also easy to locate and operate more smoothly;

Original controller, backup sensors, redundancy control, ground control equipped with display, which can realize status display, fault detection and diagnosis, parameter calibration & maintenance guidance, and other functions.

Machine and components calibrate through the control system. All valves and the controller (handle) through the control system (including the initial setting and debugging).



Advantages:

- Strong load capacity: Max. loading weight is 480kg(restricted);
- Large working range: 22m;
- Strong gradeability:30%;
- High Max. driving speed: 5.2km/h;
- Easy to control, good stability, no impact, no shaking.

GTBZ26

Max. platform height	25.8m
Max. working height	27.8m
Max. horizontal reach	22m
Load capacity	250Kg(non-restricted)/480Kg(restricted)
Platform size(L × W × H)	1.45mx0.85mx1.24m
Overall dimension L × W × H(stowed)	11.54mx2.49mx2.88m
Overall weight	16442kg(2WD)/16532kg(4WD)