

# ELECTRIC SCISSOR LIFT

GTJZ0408S / GTJZ0608S

Electric powered Scissor lift

Electric motor drive with sharp appearance, very easy for operation, it apply for both outdoor and indoor work condition by its self- propelled and steering function.

Be able to move at fast and slow speed even on different operative mode. Only one operator required on the platform to control all the functions such as lifting, moving, turning etc. Compare to man lift, it is more efficiency by use less workers and reduces labor intensity.

With automatic alarm to remind pinching hurt when the platform get down. The product large carry capacity and lower weight, the platform is dismantlable and easy for transportation.

## Advantages:

- Original imported battery can be used for more than 8 hours under general condition;
- User friendly, the lift can work when the tilt angle is within 3 degrees longitudinal and 1.5 degrees lateral;
- Self- Lubrication bearings for junction, free of maintenance.



## HIGH EFFICIENCY AND ENERGY SAVING

Adapted to advanced energy-saving technology, the product is more efficiency and energy saving.

The battery is imported from USA and can be used for more than 8 hours under general work condition. Internally installed smart charger with 100-240V voltage, and a battery indicator light of fault diagnosis.

With the battery meter the user could easily notice the battery volume and the working hour remaining. It could work while be charging.

## Advantages:

- Original imported battery can be used for more than 8 hours under general condition;
- User friendly, the lift can work when the tilt angle is within 3 degrees longitudinal and 1.5 degrees lateral;
- Self- Lubrication bearings for junction, free of maintenance; The working platform is made from pattern-steel plate which improves the antiskid effect. The drain hole on the platform prevents ponding.



### GTJZ0408S

Max. platform height	4.6m
Max. working height	6.6m
Load capacity	280kg
Platform size (LxWxH)	1.64mx0.76mx1.1m
Overall dimension Lx W (stowed)	1.775mx0.76m
Overall weight (for indoor use only)	1248kg
Power unit	24V DC , 3kW

### GTJZ0608S

Max. platform height	5.8m
Max. working height	7.8m
Load capacity	230kg
Platform size (LxWxH)	1.64mx0.76mx1.1m
Overall dimension Lx W (stowed)	1.775mx0.76m
Overall weight (for indoor use only)	1328kg
Power unit	24VDC , 3kW